



# COMMERCIAL GRADE MORTAR REPAIR TUBE

Designed for tuck-pointing, repairing, and sealing mortar joints and cracks in masonry units

©AKONA MANUFACTURING LLC • September 2008 Version 1.0

## Product Description

Akona® Pre-Mixed Mortar Repair is designed for tuck-pointing, repairing, and sealing mortar joints and cracks in masonry units such as stone, brick and block walls. The product is gray in color and designed to blend in with the texture of surrounding mortar. Pre-Mixed Mortar Repair is a sanded acrylic formulation that is fast drying, paintable and provides superior adhesion to masonry.

## When/Where to Use

- Fills mortar joints
- Vertical repairs
- Masonry finish

## Advantages

- Ready to use
- Superior adhesion
- Durable & flexible
- Fast drying

## Available Sizes:

10 FL. Oz. (296 mL) tube



## Coverage

10 linear feet (3 M) at 3/8" x 3/8" (10mm x 10mm) joint.

## Preparation:

Remove all loose or unsound materials. Thoroughly clean surface of dirt, dust, grease or other contaminants. Be sure to remove all loose chips or stones from the joint prior to using Akona® Commercial Grade Mortar Repair.

## Application

- Trim cartridge to desired bead size. Use cartridge in standard caulking gun.
- Use in joints of maximum width and depth of 3/8" (10 mm). Deep cracks can be partially filled with sand prior to application.
- The repair can be tooled to even out the surface.
- Excess material may be cleaned with a damp cloth.

## Clean Up

Typically water will satisfactorily clean tools after using Akona® Commercial Grade Mortar Repair if the material has begun to harden, warm soapy water may be helpful for cleaning hands and tools.

## For Best Results

Do not use for structural repairs to a badly damaged wall. Wait at least 24 hours before painting. Use latex paints only. Air and surface temperature should be above 40°F (4°C) for proper application. Do not apply if rain threatens or is predicted within 12 hours. Store between 35°F and 100°F (2°C and 38°C)



## Warranty:

Seller warrants that its product will conform to and perform in accordance with the product specifications. The foregoing warranty is in lieu of all other warranties, express or implied, including, but not limited to, those including merchantability and fitness for a particular purpose. Because of the difficulty in ascertaining and measuring damages hereunder, it is agreed that, seller's liability to the buyer at no point for any particular project shall exceed the total purchase price of said product.

**WARNING: INJURIOUS TO EYES!**

**KEEP OUT OF REACH OF CHILDREN!**

## PRECAUTIONS:

Avoid contact with eyes and skin. If contact with eyes occurs, flood eyes repeatedly with clean water and see a physician immediately. Do not rub eyes. Wash hands thoroughly after handling or before eating with warm, soapy water. Do not take internally. Keep out of reach of children.



## Helpful Items:

