

Product Description

Akona® Penetrating Paver & Masonry Sealer works below the surface to significantly reduce moisture absorption into the masonry or concrete being protected. After the product cures, it forms a nearly invisible barrier to minimize defects and freeze-thaw damage while creating a surface that is more readily cleaned.

When/Where to Use

Ideally suited for sealing:

- Pavers
- Brick masonry
- Stone masonry
- Concrete

Advantages

- Water-based design
- Repels water in concrete & masonry
- Reduces cleaning
- Minimizes freeze-thaw damage
- Breathable sealer

Available Sizes:

1gal. bottle

Coverage

100 - 125 sq. ft. per gallon based on application technique and surface porosity.

Preparation:

Always remove all loose and unsound materials. Protect surfaces not intended to be treated such as, vegetation, windows, vehicles, etc. from possible damage. Thoroughly clean all surfaces of dirt, dust, grease or other contaminants. Wear eye protection and rubber gloves when applying restoration products. New

masonry units or concrete should not be treated for approximately 30 days to allow these products to cure/dry. Do not apply to surfaces subject to hydrostatic pressure. For removing efflorescence or mineral deposits, it is advisable to use Akona® Concrete/Masonry Restoration Cleaner prior to using this product. For removing oil or other stains, it is advisable to use Akona® Concrete Cleaner & Degreaser prior to using this product.

Mixing

Slowly stir product before use. Do not create bubbles or foaming by shaking the product.

Application

For best results, apply when temperatures are above 50°F within 48 hours of application or when rain is not expected within 24 hours. Akona® Penetrating Paver & Masonry Sealer cures by air drying; therefore, cooler temperatures will retard drying while higher temperatures will accelerate drying. Application can be achieved with a brush, roller or sprayer. Uneven application of this product may lead to uneven appearance. In general, application of a thinner sealer coat is preferred over a thicker coat. Very porous surfaces may require two coats. Apply second coat as soon as first coat is dry to the touch. Protect newly coated areas from use for a minimum of 12 hours. Water resistance of this product will build over the first 3-4 days. Use warm, soapy water for clean-up. On larger areas, work small sections at a time. When not using this sealer, keep lid on and stored away from children.

Clean Up

Typically water will satisfactorily clean tools after using Akona® Penetrating Paver and Masonry Sealer. If the material has begun to harden, warm soapy water may be helpful for cleaning hands and tools.



Warranty:

Seller warrants that its product will conform to and perform in accordance with the product specifications. The foregoing warranty is in lieu of all other warranties, express or implied, including, but not limited to, those including merchantability and fitness for a particular purpose. Because of the difficulty in ascertaining and measuring damages hereunder, it is agreed that, seller's liability to the buyer at no point for any particular project shall exceed the total purchase price of said product.

WARNING: INJURIOUS TO EYES!

KEEP OUT OF REACH OF CHILDREN!

PRECAUTIONS:

Avoid contact with eyes and skin. If contact with eyes occurs, flood eyes repeatedly with clean water and see a physician immediately. Do not rub eyes. Wash hands thoroughly after handling or before eating with warm, soapy water. Do not take internally. Keep out of reach of children.



Helpful Items:

