

Product Description

Akona® Fast-Setting Floor Underlayment Patch is a flowable, squeegee-grade, polymer-modified patching and resurfacing underlayment. Akona® Fast-Setting Floor Underlayment Patch is easy to mix and corrects defects on concrete surfaces prior to applying new flooring materials or coatings. For deeper repairs in concrete floors, it is advisable to use Akona® Instant Patching Cement prior to using this product.

When/Where to Use

- Interior & exterior repairs
- Use to correct defects in concrete surfaces prior to applying new flooring materials or coatings.

Advantages

- Polymer-Modified for adhesion
- Flowable, reduces trowel marks
- Easily applied to surfaces
- Add water mix and use

Available Sizes:


50lb. Pail

Coverage

1 lb. will yield 1 sq. ft at 1/8" thickness.



Helpful Items:



Preparation:

Remove all loose or unsound materials. Thoroughly clean all surfaces and substrates of dirt, dust, grease or other contaminants before applying underlayment patch. Smooth troweled or dense concrete surfaces must be etched or roughened to ensure proper bond adhesion. ALWAYS PRE-WET SURFACE JUST PRIOR TO APPLICATION-NO STANDING WATER.

Mixing

Package contains two 25 pound plastic bags. Mix 2 quarts of clean water per 25 pound bag using a low speed, hand mixer until a smooth, creamy, lump-free, flowable consistency is achieved. Adding additional water or over mixing may result in decreased strength and possible cracking.

Application

For best results, apply when temperatures are above 50°F within 48 hours of application or when rain is not expected within 24 hours. Pre-dampen surface to be repaired with water just prior to application. Use a trowel or squeegee to apply the mixture to desired area. To achieve a smooth finish, apply a light touch with a freshly cleaned, damp application tool. Protect new surface from use until material is completely hard and set. Use warm, soapy water for clean-up. The initial set time is 45 minutes and the final set time is 90 minutes.

Clean Up

Typically water will satisfactorily clean tools after using Fast-Setting Floor Underlayment Patch. If the material has begun to harden, warm soapy water may be helpful for cleaning hands and tools.



Warranty:

Seller warrants that its product will conform to and perform in accordance with the product specifications. The foregoing warranty is in lieu of all other warranties, express or implied, including, but not limited to, those including merchantability and fitness for a particular purpose. Because of the difficulty in ascertaining and measuring damages hereunder, it is agreed that, seller's liability to the buyer at no point for any particular project shall exceed the total purchase price of said product.

WARNING: INJURIOUS TO EYES!

KEEP OUT OF REACH OF CHILDREN!

PRECAUTIONS:

Avoid contact with eyes and skin. If contact with eyes occurs, flood eyes repeatedly with clean water and see a physician immediately. Do not rub eyes. Wash hands thoroughly after handling or before eating with warm, soapy water. Do not take internally. Keep out of reach of children.

