

Product Description

Akona® Instant Anchoring Cement is a quick setting anchoring cement compound used for setting poles, railings, bolts and fixtures in concrete or masonry. Suitable for interior or exterior use. Expands as it hardens to set securely and lock in place for strong support.

When/Where to Use

- Interior & exterior repairs
- Sets handrails, bolts, poles, fixtures
- Concrete / Masonry

Advantages

- Expands as it hardens to set securely
- Sets in 20 minutes
- Add water mix and use

Available Sizes:

10lb. bag

Coverage

1 lb. fills approximately 17 cubic inches or anchors 2 fixtures in a 2" diameter hole with a depth of 2".



Helpful Items:



Preparation:

Remove all loose or unsound materials. Thoroughly clean surface of dirt, dust, grease or other contaminants before patching, topping, or placing overlays. Surface to be anchored must be solid. Drill and remove all loose materials from the hole. Ensure that the hole is large enough to allow cement to flow between fixture and concrete. Flush hole clean with water before adding anchoring cement. ALWAYS PRE-WET SURFACE JUST PRIOR TO APPLICATION.

Mixing

Mix approximately 2 fluid ounces of water to 1 cup of cement powder. Excessive additional water will reduce adhesion and long term durability. Always add powder to liquid to avoid lumps. Mix to a uniform consistency by hand or use a mechanical mixer until a pourable consistency is reached. Avoid high speed mixing which can entrap air into the mixture. Mix only the quantity that can be applied within 20 minutes.

Application

For best results, do not apply when temperatures will drop below 40° F within 48 hours of application. Place item to be anchored in the hole. Pour cement mixture into the hole. Compact patch, as needed, to ensure solid contact with fixture and to release any entrapped air in Akona® Instant Anchoring Cement mixture. Let set for one hour minimum before applying torque to bolt or fixture.

Clean Up

Typically water will satisfactorily clean tools after using Instant Anchoring Cement. If the material has begun to harden, warm soapy water may be helpful for cleaning hands and tools.



Warranty:

Seller warrants that its product will conform to and perform in accordance with the product specifications. The foregoing warranty is in lieu of all other warranties, express or implied, including, but not limited to, those including merchantability and fitness for a particular purpose. Because of the difficulty in ascertaining and measuring damages hereunder, it is agreed that, seller's liability to the buyer at no point for any particular project shall exceed the total purchase price of said product.

WARNING: INJURIOUS TO EYES!

KEEP OUT OF REACH OF CHILDREN!

PRECAUTIONS:

Avoid contact with eyes and skin. If contact with eyes occurs, flood eyes repeatedly with clean water and see a physician immediately. Do not rub eyes. Wash hands thoroughly after handling or before eating with warm, soapy water. Do not take internally. Keep out of reach of children.

