

Product Description

Akona® Instant Water Stop is a quick setting hydraulic cement compound used primarily as a water stop or hole filler. It expands when set and locks into place to block flowing water in 3 to 5 minutes. For use only on concrete and masonry materials.

When/Where to Use

- Plug holes in walls
- Seals water flow in basement
- Swimming pools repairs

Advantages

- Bonds to wet walls
- Sets in 3-5 minutes
- Just add water, mix and use

Available Sizes:


10 lb. and 25 lb. bags

Coverage

1 lb. fills approximately 18 cubic inches or a crack 1" deep by 1/4" wide and 6' long.



Helpful Items:



Preparation:

Remove all loose or unsound materials. Thoroughly clean surface of dirt, dust, grease or other contaminants before patching, topping, or placing overlays. Smooth troweled or dense concrete surfaces must be etched or roughened to ensure proper bond adhesion. Enlarge hole or crack to 1/2" or greater, if necessary, and make hole/crack bigger at back than on the front surface. This allows the Akona® Instant Water Stop to lock into place as it expands while setting. PRE-WET SURFACE JUST PRIOR TO APPLICATION OF PRODUCT.

Mixing

Mix only the amount of material that can be applied within 5 minutes. Hot water will accelerate setting. Mix approximately one part water to four parts Akona® Instant Water Stop. Consistency should be stiff, but thoroughly mixed with no materials left dry.

Application

For best results, do not apply when temperatures drop below 40° F within 48 hours of application. Clean up with soap and warm water as soon as application is completed. After mixing is completed, quickly apply material. Hold in place for 3-5 minutes when plugging a hole with actively flowing water.

Clean Up

Typically water will satisfactorily clean tools after using Instant Patching Cement. If the material has begun to harden, warm



soapy water may be helpful for cleaning hands and tools.

Warranty:

Seller warrants that its product will conform to and perform in accordance with the product specifications. The foregoing warranty is in lieu of all other warranties, express or implied, including, but not limited to, those including merchantability and fitness for a particular purpose. Because of the difficulty in ascertaining and measuring damages hereunder, it is agreed that, seller's liability to the buyer at no point for any particular project shall exceed the total purchase price of said product.

WARNING: INJURIOUS TO EYES!

KEEP OUT OF REACH OF CHILDREN!

PRECAUTIONS:

Avoid contact with eyes and skin. If contact with eyes occurs, flood eyes repeatedly with clean water and see a physician immediately. Do not rub eyes. Wash hands thoroughly after handling or before eating with warm, soapy water. Do not take internally. Keep out of reach of children.

