

## Product Description:

Akona® Pre-Mixed Concrete Patch is a pre-mixed, water-based formula intended to patch minor cracks, holes and surface defects in concrete or masonry. Product may also be used for residential repairs of masonry walls and re-applying small broken pieces of concrete or tuck pointing brick mortar joints. Akona® Pre-Mixed Concrete Patch offers superior adhesion and may be used for vertical or horizontal patches.

## When/Where to Use:

- Interior & exterior
- Repairs holes or cracks
- Vertical & horizontal patches
- Concrete or masonry surfaces

## Advantages:

- Ready to use
- Easy to apply
- Gray cement color
- Durable & flexible

## Available Sizes:

1 quart plastic tub



## Helpful Items:



## Coverage:

1 qt. will yield approximately 3 sq. ft. at 1/8" thickness.

## Preparation:

Thoroughly clean surface of any contaminants such as dirt, dust, oil, or loose material and all. Remove all loose chips or stones from the crack prior to using Akona® Concrete Patch. Wait until the product fully cures before painting. Prime the surface prior to applying paint on the patch.

## Application:

Gently stir product before use. Remove product directly from container and apply with a trowel or putty knife. Press firmly into patch area. Smooth finished patch with damp application tool. DO NOT OVER TROWEL. Do not apply if rain is expected or temperature is likely to fall below 50° F within 12 hours. Maximum application thickness is 1/4". For larger patches, use Akona® Vinyl Cement Patch.

## Curing/Painting:

Product will harden within a few hours. Allow about 2 days for product to fully cure when temperatures are between 65°-75°F with no rain. Use a high-quality, exterior masonry grade, breathable acrylic latex paint.

## Clean Up:

Typically water will satisfactorily clean tools after using Akona® Concrete Patch. If the material has begun to harden, warm soapy water may be helpful for cleaning hands and tools.



**WARNING: INJURIOUS TO EYES!**

**KEEP OUT OF REACH OF CHILDREN!**

## Warranty:

Seller warrants that its product will conform to and perform in accordance with the product specifications. The foregoing warranty is in lieu of all other warranties, express or implied, including, but not limited to, those including merchantability and fitness for a particular purpose. Because of the difficulty in ascertaining and measuring damages hereunder, it is agreed that, seller's liability to the buyer at no point for any particular project shall exceed the total purchase price of said product.

## Precautions:

Avoid contact with eyes and skin. If contact with eyes occurs, flood eyes repeatedly with clean water and see a physician immediately. Do not rub eyes. Wash hands thoroughly after handling or before eating with warm, soapy water. Do not take internally. Keep out of reach of children.